



CRONER MKE DUMP+CRANE TRUCK MANUAL (Long Wheelbase)

HC Class

WARRANTY

1 year unlimited mileage + 1 year or 200,000 km for powertrain

RUSTPROOFING

\$795.00

ANNUAL RUSTPROOFING INSPECTION

\$330

Annual TCD Fee

\$2,380.32

LENGTH (in.)	WIDTH (in.)	C.C	TARE (lbs.)	LOAD (lbs.)	GVW (lbs.)
248.03	90.55	5,100	15,092	9,108	24,200

»IN RELATION TO THE CRANE, PLEASE ENSURE THAT WHEN DRIVING, THE CRANE IS FACING BACKWARD«

****CALL OUR SALES STAFF ON 279-5050 FOR PRICING***

| Mon - Fri: 8am - 5pm | Sat: 9am - 1pm

**FEATURES

- Model Year 2024
- Croner MKE 11 Ton 4x2 Rigid
- 5,100c.c / 5 Litres GH5E Engine (210 hp) with turbo intercooler
- In-line 4-cylinder Diesel Engine
- Euro 3 Emission Level
- Manual 6-Speeds Transmission
- Front Parabolic Spring Chassis
- Fuel Capacity: 100 Litres (26 US Gallons)
- 2 Batteries, 110AH
- Day cab
- Wheelbase 3,750mm
- Wheel/tyre dimensions: 235/75 R17.5
- Dump Tipper 4m³ Steel Dump (**Single Panel or Split Drop Sides**)
- Air conditioning
- Power Windows
- Back-up alarm
- Tacograph preparation
- 10 Ton Jack
- Anti-lock braking system
- Radio MP3
- Transmission PTO
- Brackets only for Fire Extinguisher
- One Warning Triangle
- Standard Seat with Air Suspension
- Economy Passenger Seat
- Auxiliary Passenger Seat
- Tailgate door with automatic release

Crane Specifications

- TADANO, model # TM-ZE303MH (5 metres)
 - Capacity 3,030 kg at 2.5 m (4-parts of lines)
 - Boom:
 - Fully powered telescoping boom of pentagonal box construction
 - 3-sections
 - Length: 3.28 m - 7.71 m
 - Extending speed: 4.43 m / 12 s
 - Elevating range/speed: 1° to 78° / 7.5s
 - Max. lifting height: Approx. 9.2 m▶
 - Max. load radius: 7.5 m▶
 - Winch:
 - Hydraulic motor driven
 - Spur gear speed reduction, provided with mechanical brake
 - Max. single line pull: 7.45 kN (760 kgf)
 - Max. single line speed: 76 m/min. (at 4th layer)
 - Wire rope (Diameter x length): 8 mm x 5
 - Hydraulic System: Multiple control valves with integral safety valves
 - Slewing:
 - Hydraulic motor driven
 - Worm gear speed reduction
 - Continuous 360° full circle slewing on ball bearing slew ring
 - Automatic slewing lock
 - Slewing Speed: 2.5 min-1 {rpm}
 - Outriggers:
 - Manually extended sliders & hydraulically extended jacks
 - Integral with crane frame
 - Extension width: Max: 3.4m, Mid: 2.7m, Min: 2.0m
 - Standard Safety Devices:
 - Load meter, Load indicator, Anti-two-block alarm, Hoisting limiter, P.T.O. indicator lamp, Hook safety latch, Hydraulic safety valves, Level gauge
- ▶ Boom deflection & subsequent radius and boom angle change must be accounted for when applying load to hook

AVAILABLE COLOURS

Calm White Forest Green
 Primary Yellow Crimson Red
 Honey Yellow Blue

****ALL VEHICLES SUPPLIED INCLUDES BERMUDA SPECIFICATIONS**

| Mon - Fri: 8am - 5pm

| Sat: 9am - 1pm