



## CRONER MKE DUMP+CRANE TRUCK MANUAL (Long Wheelbase)

**HC Class**

### WARRANTY

1 year unlimited mileage + 1 year or 200,000 km for powertrain

### RUSTPROOFING

\$795.00

### ANNUAL RUSTPROOFING INSPECTION

\$330

### Annual TCD Fee

\$2,380.32

LENGTH (in.)	WIDTH (in.)	C.C	TARE (lbs.)	LOAD (lbs.)	GVW (lbs.)
248.03	90.55	5,100	15,092	9,108	24,200

**»IN RELATION TO THE CRANE, PLEASE ENSURE THAT WHEN DRIVING, THE CRANE IS FACING BACKWARD«**

**\*\*CALL OUR SALES STAFF ON 279-5050 FOR PRICING\***

| Mon - Fri: 8am - 5pm

| Sat: 9am - 1pm

## \*\*FEATURES

- Model Year 2025
- Croner MKE 11 Ton 4x2 Rigid
- 5,100c.c / 5 Litres GH5E Engine (210 hp) with turbo intercooler
- In-line 4-cylinder Diesel Engine
- Euro 3 Emission Level
- Manual 6-Speeds Transmission
- Front Parabolic Spring Chassis
- Fuel Capacity: 100 Litres (26 US Gallons)
- 2 Batteries, 1 10AH
- Day cab
- Wheelbase 3,750mm
- Wheel/tyre dimensions: 235/75 R17.5
- Dump Tipper 4m<sup>3</sup> Steel Dump (**Single Panel or Split Drop Sides**)
- Air conditioning
- Power Windows
- Back-up alarm
- Tacograph preparation
- 10 Ton Jack
- Anti-lock braking system
- Radio MP3
- Transmission PTO
- Brackets only for Fire Extinguisher
- One Warning Triangle
- Standard Seat with Air Suspension
- Economy Passenger Seat
- Auxiliary Passenger Seat
- Tailgate door with automatic release

### Crane Specifications

- TADANO, model # TM-ZE303MH (5 metres)
  - Capacity 3,030 kg at 2.5 m (4-parts of lines)
  - Boom:
    - Fully powered telescoping boom of pentagonal box construction
    - 3-sections
    - Length: 3.28 m - 7.71 m
    - Extending speed: 4.43 m / 12 s
    - Elevating range/speed: 1° to 78° / 7.5s
    - Max. lifting height: Approx. 9.2 m▶
    - Max. load radius: 7.5 m▶
  - Winch:
    - Hydraulic motor driven
    - Spur gear speed reduction, provided with mechanical brake
    - Max. single line pull: 7.45 kN (760 kgf)
    - Max. single line speed: 76 m/min. (at 4th layer)
    - Wire rope (Diameter x length): 8 mm x 5
  - Hydraulic System: Multiple control valves with integral safety valves
  - Slewing:
    - Hydraulic motor driven
    - Worm gear speed reduction
    - Continuous 360° full circle slewing on ball bearing slew ring
    - Automatic slewing lock
    - Slewing Speed: 2.5 min-1 {rpm}
  - Outriggers:
    - Manually extended sliders & hydraulically extended jacks
    - Integral with crane frame
    - Extension width: Max: 3.4m, Mid: 2.7m, Min: 2.0m
  - Standard Safety Devices:
    - Load meter, Load indicator, Anti-two-block alarm, Hoisting limiter, P.T.O. indicator lamp, Hook safety latch, Hydraulic safety valves, Level gauge
- ▶ Boom deflection & subsequent radius and boom angle change must be accounted for when applying load to hook

### AVAILABLE COLOURS

Calm White	Forest Green
Primary Yellow	Crimson Red
Honey Yellow	Blue

**\*\*ALL VEHICLES SUPPLIED INCLUDES BERMUDA SPECIFICATIONS**

| Mon - Fri: 8am - 5pm

| Sat: 9am - 1pm